



Technical Data	Standards	Clean Path
Type of Floor Covering		Modular Entrance Barrier Tile
Construction		Accuweave® Patterned Loop, ethos® modular backing
Primary Backing		Non-woven synthetic fiber
Face Weight		24 oz./sq. yd.
Gauge		1/12" (47.2 rows/10 cm)
Stitches Per Inch		8.0 stitches/inch, 31.5 stitches/10 cm
Pile Height Average		0.187" (4.8 mm)
Fiber System		TDX® Nylon
Dye Method		100% Solution Dyed
Soil/Stain Protection		Ensure
Pattern Match		N/A
Intermediate Layer		Fiberglass Reinforced Sealant
Product Construction	ASTM D 3936	No Delamination
Secondary Backing Density		65 lbs/cu ft (1041 kg/cu m)
Secondary Backing Thickness		0.050" (1.3 mm)
Total Weight		101.2 oz/sq yd +/-5% (3432 g/sq m)
Colorfastness to Light	AATCC 16E	>4 after 100 hours
Total Recycled Content		30.8% Post-Consumer
Third Party Certification		NSF-140 Platinum
CRI Green Label Plus Certification		GLP8320
TARR		3.5 Severe Traffic Classification per CRI Texture Appearance Retention Rating
Antimicrobial Chemicals	ASTM E 2471-05	No antimicrobials (EPA Registered pesticides) added to product
Electrostatic Propensity		1.5 kV (AATCC 134); Permanent Conductive Fiber
Flame Resistance	ASTM E 648	Class 1 (mean average CRF: 0.45 w/sq cm or higher)
Smoke Generation	ASTM E 662	<450
Surface Flammability	ASTM D 2859	Passes CPSC FF 1-70
Colors		2
Tile	Size Quantity Weight	24" x 24" (61 x 61 cm) 15 tiles per carton 60 lbs per carton
Warranty		1 year limited*

How to Order:
 Tile: style name – color number – color name – 24" x 24" Example: Clean Path – QA1 – Black – 24" x 24"

* Please visit www.tarkettna.com for the most updated warranty specifications, installation, cleaning and maintenance instructions.