

WPC COORDINATING MOLDINGS



WE CREATE COORDINATING MATCHES, NOT PERFECT MATCHES, BECAUSE YOUR FLOORS AND OUR MOLDINGS USE DIFFERENT PRINTING METHODS & MATERIALS.

The overall flooring assembly thickness refers to the total thickness of all members of the floor installation being laid upon the subfloor. This typically is comprised of the flooring plank, e.g. the underlayment, either attached or loose lay and any additional vapor barriers.

Slim Trim-P29

For Flooring Up to 1/4" (6.35 mm)
3-in-1: Reducer, T-Molding, & End Cap



Slim Trim-P54

For Flooring 1/4-3/8" (6.35-9.5 mm)
3-in-1: Reducer, T-Molding, & End Cap



Slim Trim-P32

For Flooring Up to 3/4" (19 mm)
3-in-1: Reducer, T-Molding, & End Cap



Available for Quick Ship

VersaEdge Extra Tall

Stair Nose - 1.5" Height



Quarter Round

Standard



Quarter Round

Moisture Proof



Slim Cap

End Cap



End Cap

Moisture Proof



Reducer

Moisture Proof



T-Molding

Moisture Proof



Versatrack Shim

Used with Versatrack
For Flooring 3/8-1/2" (9.5-12.7 mm)
Optional Use with Reducer, T-Molding, & End Cap



Versatrack

For Flooring 1/4-3/8" (6-9.5 mm)
Optional Use with Reducer, T-Molding, & End Cap



All Moldings are 94" Long

This is a custom product and is non-returnable

Technical Information

Sizes & Material

Slim Trim

Moisture Proof

Functions as a Reducer, T-Molding, and End Cap.

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: Slim Trim: PVC

SlimTrack

Included with Slim Trim-P29, Slim Cap and Slim Trim-P54

Material: Cold Roll Steel.

Versatrack Shim

1 Included with Slim Trim-P29 & Slim Cap and 2 with Slim Trim-P54

Material: Standard HDF

Dowel

Included with Slim Trim-P32

Material: Polystyrene

VersaEdge Extra Tall

Moisture Proof

Stair Nose - 1.5" Height

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: Aluminum

VT-VEX Shim - Sold Separately

Material: Standard MDF/HDF

Quarter Round

Standard or Moisture Proof

Surface Material: Decorative Paper

Core Material:

Quarter Round: Standard MDF.

Moisture Proof Quarter Round: Exterior Grade Composite Wood Product

Slim Cap

Moisture Proof

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: PVC

End Cap

Moisture Proof

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: Exterior Grade Composite Wood Product

Reducer

Moisture Proof

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: Exterior Grade Composite Wood Product

T-Molding

Moisture Proof

Surface Material: High Wear Resistant Aluminum Oxide Laminate

Core Material: Exterior Grade Composite Wood Product

Versatrack (Sold Separately)












To be used with End Cap, Reducer, and T-Molding for flooring 1/4-3/8" (6-9.5mm).

Material: Cold Roll Steel

Versatrack Shim (Sold Separately)

To be used with End Cap, Reducer, and T-Molding in conjunction with the Versatrack for flooring from 3/8-1/2" (9.5-12.7mm).

Material: Standard HDF



FOR INSTALLATION INFORMATION, TIPS, AND ADVICE GO TO: INSTALLATIONADVICE.COM